



The printed colour shades give an approximation of the end finish

Lacq ENERGOL

Authentic protection for all your outdoor wood surfaces, prepared in the traditional way. The combination of wood oil and linseed oil provides optimum results. Energol nourishes the wood from within and provides long-lasting protection. Due to the unique composition of raw materials, Energol remains flexible for a long time, allow- ing the product to flex with the surface of the wood.

Treatment:

- Surface should be dry, dust-free and grease-free. Remove any loose and defective parts. Sanding is not necessary, only if a smooth result is desired.
- Stir Energol thoroughly before use.
- Apply using a flat brush, roller or spray; to ensure a neat finish, apply Energol in the direction of the wood grain.
- Second layer can only be applied after complete drying of the first coat of approx. 16 hours. We recommend the application of three coats onto bare wood.
- After reaching the desired depth of colour in the first or second layer, Energol natural may be used to finish for maximum protection.

Touch-dry after 5 – 6 hours Paintable after approximately 16 hours (dependent upon temperature and type of wood)

Coverage: approximately 12 m² per litre

Clean tools with white spirit

Energol can be used on untreated wood and wood treated with a timber preservative.

Weathered wood should be treated in advance with a wood colour renovator.

Always sand and paint in the direction of the wood grain.





uitstrijkvermogen ergiebigkeit



water-repellent waterafstotend wasserabweisend



protection bescherming schutz



paintable overschilderbaar lackierbar



ziidealans Satin





